

(12) United States Patent Baker et al.

(10) Patent No.:

US 9,919,750 B2

(45) Date of Patent:

Mar. 20, 2018

(54) SIDE SKIRT SYSTEM FOR REDUCING

(71) Applicant: Wabash National, L.P., Lafayette, IN

(US)

(72) Inventors: Leonard W. Baker, Lafayette, IN (US);

M. Scott Stinson, Fowler, IN (US); Michael J. Courtney, Dayton, IN (US)

(73) Assignee: Wabash National, L.P., Lafayette, IN

(US)

Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/457,222

Filed: Aug. 12, 2014 (22)

(65)**Prior Publication Data**

US 2017/0174271 A1 Jun. 22, 2017

Related U.S. Application Data

- (60) Provisional application No. 61/866,220, filed on Aug. 15, 2013.
- (51) Int. Cl.

B62D 35/02 (2006.01)B62D 35/00 (2006.01)

(52) U.S. Cl.

CPC B62D 35/02 (2013.01); B62D 35/001 (2013.01); **B62D 35/008** (2013.01)

Field of Classification Search

CPC B62D 35/02
USPC
See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

357,800 A	2/1887	Wescott	
495,801 A	4/1893	Henthorne	
564,027 A	7/1896	Pratt	
824,541 A	6/1906	Hager et al.	
1,127,241 A	2/1915	Hawksworth	
2,318,863 A	5/1943	Jabelmann	
2,737,411 A	3/1956	Potter	
2,962,295 A	11/1960	Tenenbaum	
3,126,209 A	3/1964	Jewell et al.	
	(Continued)		

FOREIGN PATENT DOCUMENTS

CA	2651688 A1	7/2009
CA	2715304 A1	3/2011
CA	(Conti	

OTHER PUBLICATIONS

Office action in U.S. Appl. No. 13/847,111 dated Nov. 5, 2013 (6 pages).

(Continued)

Primary Examiner — Jason S Morrow (74) Attorney, Agent, or Firm — Quarles & Brady LLP

ABSTRACT (57)

A trailer having a storage container, a landing gear assembly coupled to the storage container, and a rear wheel assembly coupled to the storage container includes a side skirt system for reducing drag on the trailer. The side skirt system includes a side skirt wall configured to be coupled to one side of the trailer to extend below one side wall of the trailer at least partially along a length of the trailer. A length of the side skirt wall along a top edge of the side skirt wall is approximately 48%-80% of a distance between the landing gear and forward-most position of the rear wheel assembly.

16 Claims, 13 Drawing Sheets

